

### Invincible™ Hybrid PU polymer

Temperature Range: -58°F to 248°F  
 Working Pressure @ 70°F: 300 PSI  
 Burst Pressure 1200 psi  
 UV stabilized for long service life.  
 Tough and resistant to constant flexing.  
 Extremely flexible making it easier to rewind.  
 Translucent blue, allowing easy visual inspection for lubrication or contamination  
 In the field repairable hose ends eliminates down time  
 Up to 50% lighter than other hoses.  
 The most abrasion-resistant hose available.  
 Retains flexibility in subzero (-50°) temperatures.  
 Resistant to oils and greases.  
 Resistant to chemicals  
 Non-marring outer coating  
 Warranty (5yrs)  
 Cover & Tube: Premium hybrid PU polymer  
 Interlayer: Reinforced polyester

Product	Description	Item #
	1/4" ID PU hose 25 ft.	FA1425F
	1/4" ID PU hose 50 ft.	FA1450F
	1/4" ID PU hose 100 ft.	FA14100F
	3/8" ID PU hose 25 ft.	FA3825F
	3/8" ID PU hose 50 ft.	FA3850F
	3/8" ID PU hose 100 ft.	FA38100F
	1/2" ID PU hose 25 ft.	FA1225F
	1/2" ID PU hose 50 ft.	FA1250F
	1/2" ID PU hose 25 ft.	FA12100F

### Invincible™ Premium Hybrid

-40°F to 180°F  
 Lightweight, lay flat and no memory, kink resistant under pressure  
 Excellent abrasion resistant outer cover  
 Flame, UV, Ozone, cracking, chemicals and oil resistance  
 300 psi maximum working pressure, 3:1 or 4:1 safety factor  
 Bend restrictor for reducing wear and tear, and extending hose life  
 Easy coiling after use

Product	Description	Item #
	1/4" ID PU hose 25 ft.	YA1425F
	1/4" ID PU hose 50 ft.	YA1450F
	1/4" ID PU hose 100 ft.	YA14100F
	3/8" ID PU hose 25 ft.	YA3825F
	3/8" ID PU hose 50 ft.	YA3850F
	3/8" ID PU hose 100 ft.	YA38100F
	1/2" ID PU hose 25 ft.	YA1225F
	1/2" ID PU hose 50 ft.	YA1250F
	1/2" ID PU hose 100 ft.	YA12100F

### Invincible™ Rubber NBR

All weather flexibility even in sub-zero conditions: -22°F to 176°F  
 Kink resistant under pressure  
 Excellent abrasion resistant outer cover  
 Flame, UV, Ozone, cracking, chemicals and RMA class A oil resistant  
 300 psi maximum working pressure, 3:1 or 4:1 safety factor  
 Bend restrictor for reducing wear and tear, and extending hose life  
 Easy coiling after use

Product	Description	Item #
	1/4" ID NBR hose 25 ft.	GA1425F
	1/4" ID NBR hose 50 ft.	GA1450F
	1/4" ID NBR hose 100 ft.	GA14100F
	3/8" ID NBR hose 25 ft.	GA3825F
	3/8" ID NBR hose 50 ft.	GA3850F
	3/8" ID NBR hose 100 ft.	GA38100F
	1/2" ID NBR hose 25 ft.	GA1225F
	1/2" ID NBR hose 50 ft.	GA1250F
	1/2" ID NBR hose 100 ft.	GA12100F

### Invincible™ Rubber EPDM

All weather flexibility even in sub-zero conditions: -30°F to 190°F  
 Abrasion resistant outer cover  
 UV, Ozone, cracking, chemicals and RMA class C oil resistant  
 300 psi maximum working pressure, 3:1 or 4:1 safety factor  
 Bend restrictor for reducing wear and tear, and extending hose life  
 Easy coiling after use

Product	Description	Item #
	1/4" ID EPDM hose 25 ft.	EA1425F
	1/4" ID EPDM hose 50 ft.	EA1450F
	1/4" ID EPDM hose 100 ft.	EA14100F
	3/8" ID EPDM hose 25 ft.	EA3825F
	3/8" ID EPDM hose 50 ft.	EA3850F
	3/8" ID EPDM hose 100 ft.	EA38100F
	1/2" ID EPDM hose 25 ft.	EA1225F
	1/2" ID EPDM hose 50 ft.	EA1250F
	1/2" ID EPDM hose 100 ft.	EA12100F

### Invincible™ Hybrid PVC

All weather flexibility even in sub-zero conditions: -25°F to 158°F  
 Lightweight, lay flat and no memory, kink resistant under pressure  
 Abrasion resistant outer cover  
 UV, Ozone, cracking, chemicals and oil resistance  
 300 psi maximum working pressure, 3:1 safety factor  
 Bend restrictor for reducing wear and tear, and extending hose life  
 Easy coiling after use

Product	Description	Item #
	1/4" ID PVC hose 25 ft.	PA1425F
	1/4" ID PVC hose 50 ft.	PA1450F
	1/4" ID PVC hose 100 ft.	PA14100F
	3/8" ID PVC hose 25 ft.	PA3825F
	3/8" ID PVC hose 50 ft.	PA3850F
	3/8" ID PVC hose 100 ft.	PA38100F
	1/2" ID PVC hose 25 ft.	PA1225F
	1/2" ID PVC hose 50 ft.	PA1250F
	1/2" ID PVC hose 100 ft.	PA12100F

### Invincible™ PVC

Stay flexible in temperatures: -10°F to 150°F  
 Lightweight, kink resistant under pressure  
 Abrasion resistant outer cover; UV, Ozone, cracking, chemicals and oil resistance  
 300 psi maximum working pressure, 3:1 or 4:1 safety factor

Product	Description	Item #
	1/4" ID PVC hose 25 ft.	VA1425F
	1/4" ID PVC hose 50 ft.	VA1450F
	1/4" ID PVC hose 100 ft.	VA14100F
	3/8" ID PVC hose 25 ft.	VA3825F
	3/8" ID PVC hose 50 ft.	VA3850F
	3/8" ID PVC hose 100 ft.	VA38100F
	1/2" ID PVC hose 25 ft.	VA1225F
	1/2" ID PVC hose 50 ft.	VA1250F
	1/2" ID PVC hose 100 ft.	VA12100F

### Invincible™ TPR & PVC

All weather flexibility even in sub-zero conditions: -22°F to 158°F  
 Lightweight, abrasion, UV, Ozone, cracking, chemicals and oil resistance  
 300 psi maximum working pressure, 3:1 safety factor  
 High visibility for added safety around the workshop and on site  
 Manufactured in accordance with EN 2398  
 Features high grade TPR (Thermoplastic Rubber) inner tube and a clear PVC outer coating  
 Guaranteed Silicon-free for use in the body shop

Product	Description	Item #
	1/4" ID TPR & PVC hose 25 ft.	HA1425F
	1/4" ID TPR & PVC hose 50 ft.	HA1450F
	1/4" ID TPR & PVC hose 100 ft.	HA14100F
	3/8" ID TPR & PVC hose 25 ft.	HA3825F
	3/8" ID TPR & PVC hose 50 ft.	HA3850F
	3/8" ID TPR & PVC hose 100 ft.	HA38100F
	1/2" ID TPR & PVC hose 25 ft.	HA1225F
	1/2" ID TPR & PVC hose 50 ft.	HA1250F
	1/2" ID TPR & PVC hose 100 ft.	HA12100F

### Invincible™ Air Hose Reel AHRS01

Steel Construction – Heavy duty steel construction with corrosion resistant powder coating

Multiple guide arm positions provide

Non-Snag Roller – Four direction rollers reduce hose wear abrasion

Self-Laying System – Heavy duty spring powered auto rewind

Easy Mounting – Base can be mounted on wall, ceiling or floor

Adjustable Hose Stopper – Ensures the outlet hose can be set for different heights specific to the application

Product	Description	Length of hose	Item #
	3/8" ID steel auto-retractable hose reel with Invincible™ PU hybrid hose	50 ft	AHRS01-YA3815
	3/8" ID steel auto-retractable air hose reel with Invincible™ PVC hose	50 ft	AHRS01-FA3815
	3/8" ID steel auto-retractable air hose reel with Invincible™ rubber hose	50 ft	AHRS01-GA3815

### Invincible™ Air Hose Reel AHP02

PP Construction – For impact and Ozone resistance, UV stabilization and durability

Self-Laying System – For hose neat auto retraction

Optional-Position Lock – Locks the hose at any length you want

Swivel Mounting Bracket – Can be wall or ceiling mounted

Adjustable Hose Stopper – Ensures the outlet hose reachable

Product	Description	Length of hose	Item #
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PU hybrid hose	50 ft	AHP01-YA3815
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PU hose	50 ft	AHP01-FA3815
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PVC hose	50 ft	AHP01-PA3815

### Invincible™ Air Hose Reel AHRI01

PP Construction – For impact and Ozone resistance, UV stabilization and durability

Self-Laying System – For hose neat auto retraction

Optional-Position Lock – Locks the hose at any length you want

Swivel Mounting Bracket – Can be wall or ceiling mounted

Adjustable Hose Stopper – Ensures the outlet hose reachable

Product	Description	Length of hose	Item #
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PU hybrid hose	50 ft	AHP02-YA3815
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PU hose	50 ft	AHP02-FA3815
	3/8" ID polypropylene auto-retractable air hose reel with Invincible™ PVC hose	50 ft	AHP02-PA3815

### Invincible™ Air Hose Reel AHRI01

Lightweight frame construction  
Hose reel and hose is portable and manual

Foldaway reel winding handle

Ergonomic foam grip handle

360° rotation base

Rubber feet on the bottom of the base

Product	Description	Length of hose	Item #
	1/4" ID powder coated iron air hose reel with Invincible™ PU hybrid hose	100 ft	AHRI01-YA1430
	1/4" ID powder coated iron air hose reel with Invincible™ PU hose	100 ft	AHRI01-FA1430
	1/4" ID powder coated iron air hose reel with Invincible™ PVC hose	100 ft	AHRI01-PA1430